DATA SHEET

soniflex

soni EVA

Soni EVA is a soft, elastic synthetic heavy foil with special flame-retardant minerals.

Our soni EVA heavy foil is designed to eliminate vibrations and drumming of sheet metal and metal parts.



TECHNICAL DATA

FLAMMABILITY	 Fulfills the strict fire safety standard for the automotive industry (FMVSS 302, DIN 75 200) ISO 3795, burning rate < 100 mm/min ECE R-118, annexes 6, 7 and 8 fulfilled (EVA 6-01) 	
TEMPERATURE RESISTANCE	Placed on a steel surface: -50°C to +100°C, short-term up to +120°C	
HARDNESS / ISO 868	► 70 ± 5 Shore a	

DIMENSIONS

DIMENSIONS			
PRODUCT	THICKNESS / TOLERANCE [mm]	SHEETS / TOLERANCE [mm]	WEIGHT
EVA 3-01 EVA 6-01	1.5 ± 0.3 3.0 ± 0.5	1000 X 500 ± 5 1000 X 500 ± 5	3 kg/m ² ± 10% 6 kg/m ² ± 10%

ADVICE	BENEFITS
For soni EVA, the optional self-adhesive equipment of the rear face serves primarily as an installation aid. In the case of instal- lation on a vertical surface or on a ceiling, we recommend additional mechanical fixation.	 Excellent sound insulation values Very good flammability characteristics Higher temperature resistance than a bitumen layer Effortless to cut with a cardboard cutter or similar The material ist flexible, not sensitive to pressure and does not emit particles or cause smudges. Suitable for outdoor applications (if not subject to permanent sunlight exposure)
OPTIONS	SOUND TRANSMISSION LOSS
► EVA NK: no self-adhesive equipment	Our heavy layer has been designed to eliminate vibrations and drumming of


EVA SK: with self-adhesive finish

SOUND TRANSMISSION LOSS

APPLICATIONS

noise.

Test procedure similar to DIN EN ISO 354



Soni EVA is suitable specifically for technical applications, vehicles and machinery. Applied to a metal structure, soni EVA will effectively reduce the sound level and prevent

metals sheets and prevents the propagation of solid-borne sound as airborne

the transmission of noise and vibration.



PLEASE SEE OUR PROCESSING AND STORAGE INSTRUCTIONS

Details and values given in this leaflet are average values and have been compiled with care. They are not binding, however, and Cellofoam International GmbH & Co. KG disclaims any liability for any damages and detriments, also in connection with any third party's rights. The information given does not release the buyers from making the necessary experiments and tests themselves. Subject to technical changes. For updates please go to our website.

Cellofoam International GmbH & Co. KG Business unit soniflex P: +49 7351 340 28 61 sales@soniflex.de / www.soniflex.de

VERSION 07/23

Distribution partner for Switzerland: soniflex Switzerland P: +41 44 377 60 50 einkauf@soniflex.ch / www.soniflex.ch